



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification :		A2	(11) International Publication Number: WO 00/41480
Not classified			(43) International Publication Date: 20 July 2000 (20.07.00)
(21) International Application Number:	PCT/EP00/00357		[GB/GB]; 7 Menabilly Road, St Austell, Cornwall PL25 4DY (GB).
(22) International Filing Date:	13 January 2000 (13.01.00)		(74) Agent: MENES, Catherine; Etudes et Productions Schlumberger, Division Dowell, 26, rue de la Cavée, BP 202, F-92142 Clamart Cedex (FR).
(30) Priority Data:	9900904.5	16 January 1999 (16.01.99)	GB
(71) Applicant (for all designated States except CA FR US):	SOFITECH N.V. [BE/BE]; Rue de Stalle 142, B-1180 Brussels (BE).		
(71) Applicant (for CA only):	SCHLUMBERGER CANADA LIMITED [CA/CA]; 24th Floor, Monenco Place, 801 6th Avenue, S.W., Calgary, Alberta T2P 3W2 (CA).		
(71) Applicant (for FR only):	COMPAGNIE DES SERVICES DOWELL SCHLUMBERGER [FR/FR]; 50, avenue Jean-Jaurès, F-92541 Montrouge (FR).		
(72) Inventors; and			
(75) Inventors/Applicants (for US only):	SAWDON, Christopher [GB/GB]; 6 Southview Road Biscovey, Par, Cornwall PL24 2HJ (GB). TEHRANI, Mostafa [GB/GB]; 41 Trenance Road, St. Austell, Cornwall PL25 5AL (GB). CRADDOCK, Paul [GB/GB]; 193 Creak-A-Vose Park, St Stephen, St Austell, Cornwall PL26 7ND (GB). LAWSON, Anthony		
(54) Title:	ELECTRICALLY CONDUCTIVE NON-AQUEOUS WELLBORE FLUIDS		
(57) Abstract			
<p>A wellbore fluid having a non-aqueous continuous liquid phase that exhibits an electrical conductivity increased by a factor in order of 10^4 to 10^7 compared to conventional invert emulsion comprises from about 0.2 % to about 10 % by volume of carbon black particles, and one or more emulsifying surfactant(s) selected from the class including: nonionic emulsifiers of Hydrophilic-Lipophilic Balance (HLB) less than about 12, and anionic surfactants wherein the counter-ion (cation) is any of alkali metal, ammonium, or hydrogen ions. This wellbore fluid can be used for drilling or completing a well and can be used for providing enhanced information from electrical logging tools, measurement while drilling, logging while drilling, geosteering and the like.</p>			